
Evaluation of satellite data assimilation impacts within the hourly cycled Rapid Refresh

Haidao Lin
Steve Weygandt
Ming Hu
Stan Benjamin
Curtis Alexander

Assimilation and Modeling Branch Global Systems Division NOAA Earth System Research Lab Boulder, CO

Cooperative Institute for Research in the Atmosphere Colorado State University





Presentation Outline

- 1. Background on Rapid Refresh (RAP) system
- 2. Background and difficulties on regional radiance assimilation
 - → satellite data types (geo / LEO, IR / microwave)
 - → bias correction, channel selection, latency
- 3. Satellite radiance experiments
 - AIRS and GOES impact in RAP (retrospective)
 upper air and precipitation verification
 - Sensitivity to data latency (retrospective)
 upper air and precipitation verification
 - Real-time radiance impact in RAP
 upper air verification and impact on HRRR (retro)
- 4. Summary and future work

Background on Rapid Refresh NOAA/NCEP's hourly updated model

RAP version 1 -- NCEP since Spring 2012

- Advanced community codes (ARW model, GSI analysis)
- Key features for short-range "situational awareness" application (cloud analysis, radar DFI assimilation)
- → RAP guidance for aviation, severe weather, energy applications

RAP version 2 --

implemented NCEP 25 Feb. 2014


- DA enhancements (Hybrid EnKF using global ensemble)
- Model enhancements (MYNN PBL, 9-layer LSM)

RAP version 3 - planned


implementation in 2015

High Resolution Rapid Refresh (HRRR

NCEP implementation planned for later 2014




RAPv2 Data Assimilation



Rapid Refresh Hourly Update Cycle

Partial cycle atmospheric fields – introduce GFS information 2x/day


Fully cycle all land-sfc fields



Observations Used

Hourly Observations	RAP 2014 N. Amer
Rawinsonde (T,V,RH)	120
Profiler – NOAA Network (V)	21
Profiler – 915 MHz (V, Tv)	25
Radar – VAD (V)	125
Radar reflectivity - CONUS	1km
Lightning (proxy reflectivity)	NLDN, GLD360
Aircraft (V,T)	2-15K
Aircraft - WVSS (RH)	0-800
Surface/METAR (T,Td,V,ps,cloud, vis, wx)	2200- 2500
Buoys/ships (V, ps)	200-400
GOES AMVs (V)	2000- 4000
AMSU/HIRS/MHS radiances	Used
GOES cloud-top press/temp	13km
GPS – Precipitable water	260
WindSat scatterometer	2-10K

Rapid Refresh Partial Cycling



RAP Hourly cycling throughout the day

- Hourly cycling of land surface model fields
- 6-hour spin-up cycle for hydrometeors, surface fields

Radiance Data

- AMSUA (used in operational RAP)
 - Temperature and moisture information
- MHS (used in operational RAP)
 - Temperature and moisture information
- HIRS4 (used in operational RAP)
 - Temperature information
 - Moisture information (channels 10-12)

- AIRS (not in operational RAP, testing data)
 - High vertical resolution (hyperspectral)
 - Temperature and moisture information
- GOES (not in operational RAP, will be in RAP V3)
 - Temperature and moisture information
 - Good hourly real-time coverage

Radiance Assimilation for RAP

Challenges for regional, rapid updating radiance assimilation

Bias correction

- -- Sophisticated cycled predictive bias correction in GSI
- -- Spin-up period, complicated by non-uniform data coverage

Channel Selection

- Many channels sense at levels near RAP model top (10 mb)
- Use of these high peaking channel can degrade forecast
- Jacobian / adjoint analysis to select channels for exclusion

Data availability issues for real-time use

- •Rapid updating regional models: short data cut-off, small domain
- Above combined with large data latency → little data availability
- Complicates bias correction, partial cycle assimilation options

Variational Satellite Bias Correction in GSI

$$J(x,b) = \frac{1}{2}(x - x_b)^T B^{-1}(x - x_b) + \frac{1}{2}(b - b_b)^T B_b^{-1}(b - b_b)$$

$$+ \frac{1}{2}[y - \tilde{H}(x,b)]^T R^{-1}[y - \tilde{H}(x,b)]$$

$$B_{\beta} \quad \text{Bias parameter background error covariance matrix}$$

$$\tilde{H}(x,b) = H(x) + \mathop{a}\limits_{i=0}^{\infty} b_i p_i(x) + b^{scan}$$

Observation
Operator (CRTM)

Air mass bias

Angle bias


 \mathcal{D}_i are the coefficients of predictors (updated at every cycle)


$$p_i$$
 = predictors ————

mean constant (global offset) scan angle cloud liquid water (for microwave) square of T lapse rate T lapse rate

(Derber et al., 1991, Derber and Wu, 1998)

AIRS Bias Correction Assessment





--- Before BC


— After BC

channel 252 (CO2 channel ~672h Pa

Channel 1382 (water vapor channel ~866 hPa


9 day retro run averaged May08-May16 2010

AIRS Jacobians for Two Profiles



Radiance Channels Selected for RAP


- AMSU-A (remove high-peaking channels)
 - metop-a: channels 1-6, 8-10, 15
 - noaa_n15: channels 1-10, 15
 - noaa_n18: channels 1-8, 10,15
 - noaa_n19: channels 1-7, 9-10,15





- HIRS4 (remove high-peaking and ozone channels)
 - metop-a: channels: 4-8, 10-15
- MHS
 - noaa_n18, metop-a: channels 1-5;

- AIRS (remove high-peaking and ozone channels)
 - Aqua: 68 channels selected from 120 GDAS channel set
- GOES (remove high-peaking channels and ozone channel)
 - GOES-15 (sndrD1, sndrD2, sndrD3, sndrD4): channels 3-8,10-15

Real-Time Data Availability -- RARS







18Z May 29, 2013

RARS = Regional ATOVS
Retransmission Services


Assuming **+/- 1.5 h** time window

AMSU-A channel 3 from NOAA_18

Retrospective Experiments Set I: new sensors

- Extensive retro run for bias coefficients spin up
- Control run (CNTL) Conventional data only
 - 1-h cycling run, 8-day retro run (May 28 June 4 2012)
 - Hybrid EnKF RAP system
- AIRS radiance experiment
 - CNTL + AIRS radiance data (no latency)
 - Using 68 selected channels for RAP
- GOES radiance experiment
 - CNTL + real time GOES 15 radiance data (sndrD1,sndrD2,sndrD3, sndrD4)

Impact from AIRS and GOES data (against raob 100-1000 hPa)




100-1000 hPa RMS mean

upper-air verification

24-h (2 X 12h) CPC Precipitation Verification


CSI by precip threshold

(avg. over eight 24h periods)



May08-May16 2010

Sample Precipitation Impact




AIRS Ex. 2

24-h (2 X 12h) Precipitation Verification

CSI by precip threshold

(avg. over eight 24h periods)



MHS data have largest positive impact for heavy precipitation prediction


May08-May16 2010


Retrospective Experiments Set II (different data files)


- Extensive retro run for bias coefficients spin up
- Control run (CNTL) (conventional data only)
 - 1-h cycling run, 8-day retro run (May 28 June 4 2012)
 - RAP Hybrid EnKF system
- Real-time radiance (limited availability)
 - CNTL + RAP real time radiance data (amsua/mhs/hirs4/goes)
 - Use updated bias coefficients from the extensive retro run
- RARS + Real-time radiance (better availability)
 (RARS = Regional ATOVS Retransmission Services)
- Full coverage radiance (perfect availability)
 - Using full data for amsua/mhs/hirs4 (no data latency)

Coverage comparison for the RARS data and the regular feed data


Real-time radiance (limited availability)









RARS + Real-time radiance (better availability)









18Z May 29 2012 amsua noaa-19

Impact from different data sets



Impact from different data sets



May28-June04 2012 retro runs

GFS partial cycle at 09z and 21z


Precipitation Verification

Stage 4

24-h




2 x 12h fcst ending 12z



Real-time RAP Experiments

- Real-time RAP hybrid systems (RAP V2) on Zeus:
 - 1-h cycling with partial cycle
 - real-time data
- <u>6 month time period</u> (Jun-July, Oct-Dec, 2013, Jan, 2014)
- NO radiance
 - conventional data only
- WITH radiance
 - conventional data + operational used radiance data (AMSU-A, HIRS4, MHS)


Real-time % improvement from radiance DA



GFS partial cycle at 09z and 21z

100-1000 hPa RMS mean

6-h Forecast RMS Error




WITH radiance


NO radiance

upper-air verification

Real-Time 6-month average (limited data coverage)



HRRR Radar reflectivity verification



Summary of radiance updates for RAP V3

- Included new sensors/data
 - ◆GOES sounding data from GOES-15
 - amsua/mhs from noaa-19 and metop-b;
- Included the RARS data (Just on Zeus now)
- Removed some high peaking channels to fit the model top of RAP and removed the ozone channels
- Implemented the enhanced variational bias correction scheme with cycling

Conclusions

- AIRS and GOES data have slightly positive impact
- RAP real-time radiance data have slightly positive impact and the RARS data provide additional benefits
- 6-month real time runs showed consistent positive impact (around 1%) from radiance data in RAP
- Assimilation of satellite radiance data in morning RAP runs, improving mesoscale environment, leading to slightly better HRRR forecasts of convective initiation and evolution
- Recommendations for RAP V3 updates (R2O, included, planned operational implementation in 2015)

Future work

- Other new data (focusing on hyperspectral data)
 - -- ATMS and CrIS from NPP
 - -- IASI from metop-a/b
 - -- ABI from GOES-R (when available)
- Increase RAP model top and model levels for better use of hyperspectral data in regional model and better bias correction (for experiment and research purpose)

- Real-time data latency problem:
 - Partial cycle strategy
 - Use direct read out data

